

AS-7108HLS

(Single Rail, 17" HDMI LCD KVM Switch 8 Ports)



LCD Monitor Features:

- I. Front LCD Console(keyboard,mouse,monitor17")+ 8 port HDMI KVM Module design (1ports); It's very flexible and convenient for combination;
- II.Keyboard is with demountable design, with 9 different languages: American, English, German, French, Spanish, Swiss, Turkish, Russian, Italian;
- III. Extra prepositive USB mouse interface;
- IV. Total length: 611m; fit for 800-1200mm cabinet;
- V. Support 1080p resolution;

17” High-Definition Monitor Specification:

| Type | 17.3” Wide-Screen LCD Console-AS7100HLS(F) | |
|----------------------------------|--|--|
| LCD Monitor | Ratio | 17.3” Screen, 16:9 |
| | Video | Wide AHVA TFT-LCD |
| | Visible Square | 381.888(H) x 214.812(V) |
| | Resolution | 1920*1080 @60HZ |
| | Support Color | 16.7M (RGB 6-bit data+ HiFCR data) |
| | Contrast | 600 : 1 (Typ) |
| | Back light | LED |
| | Pixel Pitch | 0.1989(per one triad) x 0.1989 |
| | LED MTBF | 100,000 hours |
| | Input power | 12V |
| Keyboard (demountable design) | Keyboard | 100Keys, detachable (9 different languages for choose) |
| | Compatible IBM/AT | Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10 |
| | Port | Standard PS/2; USB |
| | Using life | >1,000,000 Times |
| Mouse | Type | Touch Screen |
| | Port | Standard PS/2 |
| | X/Y Resolution | >1000dots/inch, (40x40/mm) |
| | Using life | >1,000,000 Times |
| Installation Dimension | 407*445*45mm | |
| Weight | 8.5kg | |

HDMI KVM Module Features:

- ◆ Single USB console control 8HDMI interface computer and two additional USB device
- ◆ Supports USB TYPE A interface type keyboard and mouse device
- ◆ HDMI LCD Console resolution in Optimum:1920x1080@60Hz;
- ◆ KVM module resolution in Max: 4K@30HZ(3840x2610@30HZ);
- ◆ Switch the computer through the front panel buttons, keyboard hotkeys and screen menu (OSD)
- ◆ Connect to the controlled device for BIOS-level access without worrying about the risk of viruses and Trojans
- ◆ The controlled computer does not need to install any software and drivers, and the controlled computer directly recognizes KVM.
- ◆ Upgrade remote network control mode by extending IP BOX
- ◆ Support OSD to set user login mode and increase KVM login security requirements
- ◆ Support widescreen resolution
- ◆ Support DDC communication to adapt to different graphics devices
- ◆ Auto scan function monitors all computer operations

- ◆ Support for cross-platform operations - Windows, Linux, Mac*, and Sun*

KVM Module Specification:

| Type | | 8 Port | |
|-----------------------------|---------------------------|---|--------------------------|
| Model No.(Completed device) | | AS7100HLS(F)+HLS-H08 (AS-7108HLS) | |
| Computer Connection | | 8 | |
| Port Selection | | OSD Menu, Front panel switches, Hot Key | |
| Connector | Console Connector | Monitor | 1 x HDMI Female |
| | | Keyboard | 1 x USB Type A Female |
| | | Mouse | 1 x USB Type A Female |
| | PC Connector | Monitor | 8 x HDMI Female |
| | | Mouse/Keyboard | 8 x USB TYPE B Female |
| Power Supply | | 1 x DC Jack | |
| Key switch | Connection Port Selection | | 8 x keys |
| | KVM Switch Reset | | 1 x Semi-embedded keys |
| LED Instruction | Selected | | 8 x Green |
| | Online | | 8 x Red |
| Simulation Method | Keyboard & Mouse | | USB |
| Max Resolution Video | | 4K@30HZ (3840*2610@30HZ) | |
| Scan interval | | 3、5、10、15、20、30、40、60 seconds (Default 3 Seconds) | |
| Operating Environment | Operating temperature | | 0-50°C |
| | Storage temperature | | -20-60°C |
| | Humidity | | 0-80%RH, No Condensation |
| Physical Properties | Housing | | metal |
| | Dimensions(L x W x H) | | 432 x 155 x 44 mm |
| | Weight (kgs) | | 2.88KG |